



Modelos

Rango de Intensidad	Ref:
1 ~ 1,6 A	2772-5273
1,6 ~ 2,5 A	2772-5274
2,5 ~ 4 A	2772-5275
4 ~ 6,3 A	2772-5276
6 ~ 10 A	2772-5277
9 ~ 14 A	2772-5278
13 ~ 18 A	2772-5279

Detalles técnicos

Frecuencia	50-60 Hz	Protección IP	IP20
Intensidad de Corriente	118 A	Marca	MAXGE
Uso	Interior	Rango de Intensidad	2,5 ~ 4 A, 1,6 ~ 2,5 A, 1 ~ 1,6 A, 13 ~ 18 A, 9 ~ 14 A, 6 ~ 10 A, 4 ~ 6,3 A



Descripción







Protege contra sobrecargas (Protección térmica), cortocircuitos (Protección magnética) y fallo de fase.

Dispone de pulsador de encendido y de apagado para poder controlar el disparo de forma manual. Además se puede ajustar el rango de intensidad de trabajo. Permite ser instalado mediante enganche a perfil y conexión de cable en bornas por tornillo.

Características técnicas:

Rango

Motor (kW)

Capacidad (kA)

(A)

230VAC

400VAC

440VAC

Icu

Ics

1-1,6

0,37

0,55

100

100

1,6-2,5

0,37

0,75

1,1

100

100

2,5-4

0,75

1,5

1,5



100

100

4-6,3



Fotografías adicionales



Dimension(mm)			
H	I1	I2	
89	16	50	
w1	h1	h2	
44,5	22	45	